

1

2

3

4

5

6

Projection

Rotor Side | Stator Side

OUTLINE DIMENSION

(UNIT) mm

TYPE	QD-F-8PG-M51	QD-F-8PG-G1/8	QD-F-8PG-G1/4	QD-F-8PG-G3/8	QD-F-8PG-G1/2
A	M5	G1/8	G1/4	G3/8	G1/2
B	M6	M6	M10	M10	M10
C	55	80	85	106	111
D	65	90	95	120	125
E	22	40	48	52	55
F	43	58	68	73	88
G	2	2	2	2	2
H	50	62	67	71	80
M	17	17	20	20	20
L	151	192	231	239	297
N	5	5	8	8	8
O	34.4	37.4	41.4	47.4	49.5
P	12	17	21	25	29
Q	33+S	33+S	33+S	33+S	33+S

Working parameters:

Max.Speed: 160RPM

Max.pressure: 3500PSI

Temperature Range: 5°C to 120°C

Medium type :water Gas Oil and so on

Materials :Stainless steel

Fluid or Gas Passage:8Passage

Rated Voltage :600VDC/VAC

Compressive strength:1000VDC@50Hz

Bration level:MIL-SID-810E

lead length:UL Teflon250mm

Protection grade:IP51

Humidity:10% to 90% RH

contact material:Race metel(gold-gold)

CE Proofed:YES

Support ring size:1-96rings

1						Drawing	Design	Audit	Approval		seals	Dynamic seal		
2											material	Stainless steel	name	rotay joint
3			Size range	Allow poor			Date of publication				bearing	High speed ball bearing	number	NO.ONE
4	Change content		Date			HIDNEY ELECTRONICS					weight		Model	

1

2

3

4

5

6

D